Honeywell

LC407-1 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4 Revision Date 04/08/2014 Print Date 02/25/2016

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name 0.1% Trifluoroacetic Acid in Acetonitrile

MSDS Number 000000011215

Product Use Description Solvent

Manufacturer or supplier's

details

Honeywell International Inc.

115 Tabor Road

Morris Plains, NJ 07950-2546

For more information call 1-800-368-0050

(Monday-Friday, 9:00am-5:00pm)

In case of emergency call: Medical: 1-800-498-5701 or +1-303-389-1414

Transportation (CHEMTREC): 1-800-424-9300 or

+1-703-527-3887

(24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form : liquid

Color : colourless

: sweet ether-like Odor

Classification of the substance or mixture

or mixture

Classification of the substance : Flammable liquids, Category 2 Eye irritation, Category 2A

Specific target organ toxicity - single exposure, Category 1,

Central nervous system, Respiratory system

Specific target organ toxicity - repeated exposure, Category 2, Central nervous system, Respiratory system, Kidney, Blood,

Liver

Page 1 / 14

Honeywell

LC407-1 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4 Revision Date 04/08/2014 Print Date 02/25/2016

GHS Label elements, including precautionary statements

Symbol(s) :







Signal word : Danger

Hazard statements : Highly flammable liquid and vapour.

Causes serious eye irritation. Causes damage to organs.

May cause damage to organs through prolonged or repeated

exposure.

Precautionary statements : Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No

smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Do not eat, drink or smoke when using this product. Wear protective gloves/ eye protection/ face protection.

Response:

IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

IF exposed: Call a POISON CENTER or doctor/ physician. If eye irritation persists: Get medical advice/ attention.

In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam for extinction.

Storage:

Store in a well-ventilated place. Keep cool.

Store locked up.

Honeywell

LC407-1 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4 Revision Date 04/08/2014 Print Date 02/25/2016

Disposal:

Dispose of contents/ container to an approved waste disposal

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture

Chemical Name	CAS-No.	Concentration
Acetonitrile	75-05-8	>99.00 %
Trifluoroacetic acid	76-05-1	0.035 - 0.10 %

SECTION 4. FIRST AID MEASURES

Inhalation : Remove to fresh air. If not breathing, give artificial respiration. If

breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present. Call a physician.

Skin contact : Wash off immediately with plenty of water for at least 15

minutes. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. Call a physician.

Eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes. Call a physician.

Ingestion : Call a physician. Do not induce vomiting without medical advice.

Immediate medical attention is required. Never give anything by

mouth to an unconscious person.

Notes to physician

Honeywell

LC407-1 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4 Revision Date 04/08/2014 Print Date 02/25/2016

Treat as cyanide poisoning. Symptoms of poisoning may not

appear for several hours. Keep under medical supervision for at

least 48 hours.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide (CO2)

Dry chemical

Alcohol-resistant foam

Cool closed containers exposed to fire with water spray.

Unsuitable extinguishing

media

: Do not use a solid water stream as it may scatter and spread

fire.

Specific hazards during

firefighting

: Flammable.

Vapours may form explosive mixtures with air.

Vapours are heavier than air and may spread along floors. Vapors may travel to areas away from work site before

igniting/flashing back to vapor source.

In case of fire hazardous decomposition products may be

produced such as:

Hydrogen cyanide (hydrocyanic acid)

Carbon dioxide (CO2), carbon monoxide (CO), oxides of

nitrogen (NOx), dense black smoke.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus and protective suit.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear personal protective equipment.

Immediately evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.

Ensure adequate ventilation. Remove all sources of ignition.

Do not swallow.

Avoid breathing vapours, mist or gas. Avoid contact with skin, eyes and clothing.

Environmental precautions : Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Page 4 / 14

Honeywell

LC407-1 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4 Revision Date 04/08/2014 Print Date 02/25/2016

Discharge into the environment must be avoided.

Do not flush into surface water or sanitary sewer system. Do not allow run-off from fire fighting to enter drains or water

courses.

Methods for cleaning up : Ventilate the area.

No sparking tools should be used. Use explosion-proof equipment.

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national

regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Handling

Handling : Wear personal protective equipment.

Use only in well-ventilated areas. Keep container tightly closed.

Do not smoke. Do not swallow.

Avoid breathing vapours, mist or gas. Avoid contact with skin, eyes and clothing.

Advice on protection against :

fire and explosion

Keep away from fire, sparks and heated surfaces.

Take precautionary measures against static discharges.

Ensure all equipment is electrically grounded before beginning

transfer operations.

Use explosion-proof equipment.

Keep product and empty container away from heat and sources

of ignition.

No sparking tools should be used.

No smoking.

Storage

Requirements for storage areas and containers

Store in area designed for storage of flammable liquids. Protect

from physical damage.

Keep containers tightly closed in a dry, cool and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.



LC407-1 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4 Revision Date 04/08/2014 Print Date 02/25/2016

Keep away from heat and sources of ignition.

Keep away from direct sunlight.

Store away from incompatible substances.

Container hazardous when empty.

Do not pressurize, cut, weld, braze, solder, drill, grind or expose

containers to heat or sources of ignition.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Ensure that eyewash stations and safety showers are close to

the workstation location.

Engineering measures : Use with local exhaust ventilation.

Prevent vapour buildup by providing adequate ventilation during

and after use.

Eye protection : Do not wear contact lenses.

Wear as appropriate:

Safety glasses with side-shields If splashes are likely to occur, wear:

Goggles or face shield, giving complete protection to eyes

Hand protection : Solvent-resistant gloves

Gloves must be inspected prior to use.

Replace when worn.

Skin and body protection : Wear as appropriate:

Solvent-resistant apron

Flame retardant antistatic protective clothing

If splashes are likely to occur, wear:

Protective suit

Respiratory protection : In case of insufficient ventilation, wear suitable respiratory

equipment.

For rescue and maintenance work in storage tanks use

self-contained breathing apparatus.

Use NIOSH approved respiratory protection.

Hygiene measures : When using do not eat, drink or smoke.

Wash hands before breaks and immediately after handling the

product.

Keep working clothes separately.

Remove and wash contaminated clothing before re-use.

Page 6 / 14

Honeywell

LC407-1 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4 Revision Date 04/08/2014 Print Date 02/25/2016

Do not swallow. Avoid breathing vapours, mist or gas. Avoid contact with skin, eyes and clothing.

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Upda te	Basis
Acetonitrile	75-05-8	TWA: time weighted average	(20 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values
Acetonitrile	75-05-8	SKIN_DE S : Skin designati on:	Can be absorbed through the skin.	2008	ACGIH:US. ACGIH Threshold Limit Values
Acetonitrile	75-05-8	REL: Recomm ended exposure limit (REL):	34 mg/m3 (20 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards
Acetonitrile	75-05-8	PEL: Permissi ble exposure limit	70 mg/m3 (40 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
Acetonitrile	75-05-8	TWA: time weighted average	70 mg/m3 (40 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)
Acetonitrile	75-05-8	STEL: Short term exposure limit	105 mg/m3 (60 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)

Honeywell

LC407-1 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4 Revision Date 04/08/2014 Print Date 02/25/2016

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Color : colourless

Odor : sweet ether-like

pH : Note: not applicable

Melting point/freezing point : -46 °C

Boiling point/boiling range : 82 °C

Flash point : 43 °F (6 °C)

Method: closed cup

Note: The physical data is that of the main component.

Evaporation rate : 5

Method: Compared to Butyl acetate.

Lower explosion limit : 3 %(V)

Note: The physical data is that of the main component.

Upper explosion limit : 16 %(V)

Note: The physical data is that of the main component.

Vapor pressure : 97 hPa

at 20 °C(68 °F)

Vapor density : 1.42 Note: (Air = 1.0)

Density : 0.782 g/cm3 at 20 °C

0.777 g/cm3 at 25 °C

Honeywell

LC407-1 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4 Revision Date 04/08/2014 Print Date 02/25/2016

Water solubility : Note: completely soluble

Ignition temperature : 524 °C

Note: The physical data is that of the main component.

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under normal conditions.

Possibility of hazardous

Conditions to avoid

reactions

: Hazardous polymerisation does not occur.

: Heat, flames and sparks. Keep away from direct sunlight.

Incompatible materials to

avoid

: Acids Bases

> Oxidizing agents Reducing agents

Sulfites
Perchlorates

May attack many plastics, rubbers and coatings.

Hazardous decomposition

products

: In case of fire hazardous decomposition products may be

produced such as:

Hydrogen cyanide (hydrocyanic acid)

Carbon dioxide (CO2), carbon monoxide (CO), oxides of

nitrogen (NOx), dense black smoke.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

Acetonitrile : LD50: 2,460 mg/kg

Species: rat

Trifluoroacetic acid : LDLo: 500 mg/kg

Page 9 / 14

Honeywell

LC407-1 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4 Revision Date 04/08/2014 Print Date 02/25/2016

Species: rat

Acute inhalation toxicity

Acetonitrile : LC50: 16000 ppm

Exposure time: 4 h

Species: rat

Trifluoroacetic acid : LC50: 10 mg/l

Species: rat

Acute dermal toxicity

Acetonitrile : LD50: > 2,000 mg/kg

Species: rabbit

Eye irritation

Acetonitrile : Species: rabbit

Result: Irritating to eyes.

SECTION 12. ECOLOGICAL INFORMATION

Toxicity to fish

Acetonitrile : flow-through test

LC50: 1,640 mg/l Exposure time: 96 h

Species: Pimephales promelas (fathead minnow)

Further information on ecology

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Observe all Federal, State, and Local Environmental

regulations.

Page 10 / 14

Honeywell

LC407-1 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4 Revision Date 04/08/2014 Print Date 02/25/2016

SECTION 14. TRANSPORT INFORMATION

: UN 1648 DOT UN/ID No.

> Proper shipping name : ACETONITRILE SOLUTION

Class 3 Packing group Ш Hazard Labels 3

IATA UN/ID No. : UN 1648

> Description of the goods : ACETONITRILE SOLUTION

Class : 3 Packaging group : 11 Hazard Labels : 3 : 364

Packing instruction (cargo

aircraft)

Packing instruction : 353

(passenger aircraft)

Packing instruction : Y341

(passenger aircraft)

IMDG UN/ID No. : UN 1648

> Description of the goods : ACETONITRILE SOLUTION

Class : 3 Packaging group : 11 Hazard Labels : 3

EmS Number : F-E, S-D Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

Inventories

US. Toxic Substances : On TSCA Inventory

Control Act

Australia. Industrial : On the inventory, or in compliance with the inventory

Chemical (Notification and

Assessment) Act

Canada. Canadian : All components of this product are on the Canadian DSL.

Environmental Protection

Page 11 / 14

Honeywell

LC407-1 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4 Revision Date 04/08/2014 Print Date 02/25/2016

Act (CEPA). Domestic Substances List (DSL)

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Toxic Chemical Control Law (TCCL) List : On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control

: On the inventory, or in compliance with the inventory

Act

Chemical Substances

China. Inventory of Existing : On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New

Zealand

: On the inventory, or in compliance with the inventory

National regulatory information

US. EPA CERCLA

Hazardous Substances (40

CFR 302)

: The following component(s) of this product is/are subject to release reporting under 40 CFR 302 when release exceeds the

Reportable Quantity (RQ):

Reportable quantity: 5000 lbs

Acetonitrile 75-05-8

SARA 302 Components

SARA 313 Components

: Acetonitrile 75-05-8

SARA 311/312 Hazards : Fire Hazard

> Acute Health Hazard Chronic Health Hazard

CERCLA Reportable

Quantity

: 5005 lbs

Honeywell

LC407-1 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4 Revision Date 04/08/2014 Print Date 02/25/2016

California Prop. 65 : WARNING! This product contains a chemical known to the State

of California to cause cancer.

Acrylonitrile 107-13-1

Massachusetts RTK : Acetonitrile 75-05-8

New Jersey RTK : Acetonitrile 75-05-8

Pennsylvania RTK : Acetonitrile 75-05-8

WHMIS Classification : B2: Flammable liquid

D1A: Very Toxic Material Causing Immediate and Serious Toxic

Effects

D2B: Toxic Material Causing Other Toxic Effects

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required

by the CPR.

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 2*	2
Flammability	: 3	3
Physical Hazard	: 0	
Instability	:	0

^{* -} Chronic health hazard

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe

Honeywell

LC407-1 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4 Revision Date 04/08/2014 Print Date 02/25/2016

handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 07/01/2011

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group