

LC407-2.5 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4

Revision Date 04/08/2014

Print Date 02/25/2016

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : 0.1% Trifluoroacetic Acid in Acetonitrile

MSDS Number : 000000011215

Product Use Description : Solvent

Manufacturer or supplier's details : Honeywell International Inc.
115 Tabor Road
Morris Plains, NJ 07950-2546

For more information call : 1-800-368-0050
(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : **Medical: 1-800-498-5701 or +1-303-389-1414**
: **Transportation (CHEMTREC): 1-800-424-9300 or**
: **+1-703-527-3887**
:
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION**Emergency Overview**

Form : liquid

Color : colourless

Odor : sweet ether-like

Classification of the substance or mixture

Classification of the substance or mixture : Flammable liquids, Category 2
Eye irritation, Category 2A
Specific target organ toxicity - single exposure, Category 1,
Central nervous system, Respiratory system
Specific target organ toxicity - repeated exposure, Category 2,
Central nervous system, Respiratory system, Kidney, Blood,
Liver

LC407-2.5 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4

Revision Date 04/08/2014

Print Date 02/25/2016

GHS Label elements, including precautionary statements

Symbol(s)

:



Signal word

: Danger

Hazard statements

: Highly flammable liquid and vapour.
Causes serious eye irritation.
Causes damage to organs.
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

: **Prevention:**
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting/ equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Wash skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Wear protective gloves/ eye protection/ face protection.

Response:

IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed: Call a POISON CENTER or doctor/ physician.
If eye irritation persists: Get medical advice/ attention.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

Store in a well-ventilated place. Keep cool.
Store locked up.

LC407-2.5 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4

Revision Date 04/08/2014

Print Date 02/25/2016

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture

Chemical Name	CAS-No.	Concentration
Acetonitrile	75-05-8	>99.00 %
Trifluoroacetic acid	76-05-1	0.035 - 0.10 %

SECTION 4. FIRST AID MEASURES

- Inhalation : Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present. Call a physician.
- Skin contact : Wash off immediately with plenty of water for at least 15 minutes. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. Call a physician.
- Eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Call a physician.
- Ingestion : Call a physician. Do not induce vomiting without medical advice. Immediate medical attention is required. Never give anything by mouth to an unconscious person.

Notes to physician

LC407-2.5 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4

Revision Date 04/08/2014

Print Date 02/25/2016

Treatment : Treat as cyanide poisoning. Symptoms of poisoning may not appear for several hours. Keep under medical supervision for at least 48 hours.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Carbon dioxide (CO₂)
Dry chemical
Alcohol-resistant foam
Cool closed containers exposed to fire with water spray.

Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

Specific hazards during firefighting : Flammable.
Vapours may form explosive mixtures with air.
Vapours are heavier than air and may spread along floors.
Vapors may travel to areas away from work site before igniting/flashing back to vapor source.
In case of fire hazardous decomposition products may be produced such as:
Hydrogen cyanide (hydrocyanic acid)
Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

Special protective equipment for firefighters : Wear self-contained breathing apparatus and protective suit.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Wear personal protective equipment.
Immediately evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not swallow.
Avoid breathing vapours, mist or gas.
Avoid contact with skin, eyes and clothing.

Environmental precautions : Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.

LC407-2.5 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4

Revision Date 04/08/2014

Print Date 02/25/2016

Discharge into the environment must be avoided.
Do not flush into surface water or sanitary sewer system.
Do not allow run-off from fire fighting to enter drains or water courses.

Methods for cleaning up : Ventilate the area.
No sparking tools should be used.
Use explosion-proof equipment.
Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE**Handling**

Handling : Wear personal protective equipment.
Use only in well-ventilated areas.
Keep container tightly closed.
Do not smoke.
Do not swallow.
Avoid breathing vapours, mist or gas.
Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion : Keep away from fire, sparks and heated surfaces.
Take precautionary measures against static discharges.
Ensure all equipment is electrically grounded before beginning transfer operations.
Use explosion-proof equipment.
Keep product and empty container away from heat and sources of ignition.
No sparking tools should be used.
No smoking.

Storage

Requirements for storage areas and containers : Store in area designed for storage of flammable liquids. Protect from physical damage.
Keep containers tightly closed in a dry, cool and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.

LC407-2.5 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4

Revision Date 04/08/2014

Print Date 02/25/2016

Keep away from heat and sources of ignition.
Keep away from direct sunlight.
Store away from incompatible substances.
Container hazardous when empty.
Do not pressurize, cut, weld, braze, solder, drill, grind or expose
containers to heat or sources of ignition.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- | | |
|--------------------------|---|
| Protective measures | : Ensure that eyewash stations and safety showers are close to the workstation location. |
| Engineering measures | : Use with local exhaust ventilation.
Prevent vapour buildup by providing adequate ventilation during and after use. |
| Eye protection | : Do not wear contact lenses.
Wear as appropriate:
Safety glasses with side-shields
If splashes are likely to occur, wear:
Goggles or face shield, giving complete protection to eyes |
| Hand protection | : Solvent-resistant gloves
Gloves must be inspected prior to use.
Replace when worn. |
| Skin and body protection | : Wear as appropriate:
Solvent-resistant apron
Flame retardant antistatic protective clothing
If splashes are likely to occur, wear:
Protective suit |
| Respiratory protection | : In case of insufficient ventilation, wear suitable respiratory equipment.
For rescue and maintenance work in storage tanks use self-contained breathing apparatus.
Use NIOSH approved respiratory protection. |
| Hygiene measures | : When using do not eat, drink or smoke.
Wash hands before breaks and immediately after handling the product.
Keep working clothes separately.
Remove and wash contaminated clothing before re-use. |

LC407-2.5 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4

Revision Date 04/08/2014

Print Date 02/25/2016

Do not swallow.
Avoid breathing vapours, mist or gas.
Avoid contact with skin, eyes and clothing.

Exposure Guidelines

Components	CAS-No.	Value	Control parameters	Update	Basis
Acetonitrile	75-05-8	TWA : time weighted average	(20 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values

Acetonitrile	75-05-8	SKIN_DES : Skin designation:	Can be absorbed through the skin.	2008	ACGIH:US. ACGIH Threshold Limit Values
--------------	---------	------------------------------	-----------------------------------	------	--

Acetonitrile	75-05-8	REL : Recommended exposure limit (REL):	34 mg/m3 (20 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards
--------------	---------	---	-------------------	------	---

Acetonitrile	75-05-8	PEL : Permissible exposure limit	70 mg/m3 (40 ppm)	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
--------------	---------	----------------------------------	-------------------	---------	--

Acetonitrile	75-05-8	TWA : time weighted average	70 mg/m3 (40 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)
--------------	---------	-----------------------------	-------------------	------	---

Acetonitrile	75-05-8	STEL : Short term exposure limit	105 mg/m3 (60 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)
--------------	---------	----------------------------------	--------------------	------	---

LC407-2.5 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4

Revision Date 04/08/2014

Print Date 02/25/2016

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Color	: colourless
Odor	: sweet ether-like
pH	: Note: not applicable
Melting point/freezing point	: -46 °C
Boiling point/boiling range	: 82 °C
Flash point	: 43 °F (6 °C) Method: closed cup Note: The physical data is that of the main component.
Evaporation rate	: 5 Method: Compared to Butyl acetate.
Lower explosion limit	: 3 %(V) Note: The physical data is that of the main component.
Upper explosion limit	: 16 %(V) Note: The physical data is that of the main component.
Vapor pressure	: 97 hPa at 20 °C(68 °F)
Vapor density	: 1.42 Note: (Air = 1.0)
Density	: 0.782 g/cm ³ at 20 °C 0.777 g/cm ³ at 25 °C

LC407-2.5 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4

Revision Date 04/08/2014

Print Date 02/25/2016

Water solubility : Note: completely soluble

Ignition temperature : 524 °C
Note: The physical data is that of the main component.

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Hazardous polymerisation does not occur.

Conditions to avoid : Heat, flames and sparks.
Keep away from direct sunlight.

Incompatible materials to avoid : Acids
Bases
Oxidizing agents
Reducing agents
Sulfites
Perchlorates
May attack many plastics, rubbers and coatings.

Hazardous decomposition products : In case of fire hazardous decomposition products may be produced such as:
Hydrogen cyanide (hydrocyanic acid)
Carbon dioxide (CO₂), carbon monoxide (CO), oxides of nitrogen (NO_x), dense black smoke.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity
Acetonitrile : LD50: 2,460 mg/kg
Species: rat

Trifluoroacetic acid : LDLo: 500 mg/kg

LC407-2.5 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4

Revision Date 04/08/2014

Print Date 02/25/2016

Species: rat

Acute inhalation toxicity
Acetonitrile: LC50: 16000 ppm
Exposure time: 4 h
Species: rat

Trifluoroacetic acid

: LC50: 10 mg/l
Species: ratAcute dermal toxicity
Acetonitrile: LD50: > 2,000 mg/kg
Species: rabbitEye irritation
Acetonitrile: Species: rabbit
Result: Irritating to eyes.**SECTION 12. ECOLOGICAL INFORMATION**Toxicity to fish
Acetonitrile: flow-through test
LC50: 1,640 mg/l
Exposure time: 96 h
Species: Pimephales promelas (fathead minnow)**Further information on ecology****SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods

: Observe all Federal, State, and Local Environmental regulations.

LC407-2.5 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4

Revision Date 04/08/2014

Print Date 02/25/2016

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 1648
Proper shipping name : ACETONITRILE SOLUTION
Class : 3
Packing group : II
Hazard Labels : 3

IATA UN/ID No. : UN 1648
Description of the goods : ACETONITRILE SOLUTION
Class : 3
Packaging group : II
Hazard Labels : 3
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353
Packing instruction (passenger aircraft) : Y341

IMDG UN/ID No. : UN 1648
Description of the goods : ACETONITRILE SOLUTION
Class : 3
Packaging group : II
Hazard Labels : 3
EmS Number : F-E, S-D
Marine pollutant : no

SECTION 15. REGULATORY INFORMATION**Inventories**

US. Toxic Substances : On TSCA Inventory
Control Act

Australia. Industrial : On the inventory, or in compliance with the inventory
Chemical (Notification and
Assessment) Act

Canada. Canadian : All components of this product are on the Canadian DSL.
Environmental Protection

LC407-2.5 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4

Revision Date 04/08/2014

Print Date 02/25/2016

Act (CEPA). Domestic
Substances List (DSL)

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Toxic Chemical
Control Law (TCCL) List : On the inventory, or in compliance with the inventory

Philippines. The Toxic
Substances and Hazardous
and Nuclear Waste Control
Act : On the inventory, or in compliance with the inventory

China. Inventory of Existing
Chemical Substances : On the inventory, or in compliance with the inventory

New Zealand. Inventory of
Chemicals (NZIoC), as
published by ERMA New
Zealand : On the inventory, or in compliance with the inventory

National regulatory information

US. EPA CERCLA
Hazardous Substances (40
CFR 302) : The following component(s) of this product is/are subject to
release reporting under 40 CFR 302 when release exceeds the
Reportable Quantity (RQ):

Reportable quantity: 5000 lbs
: Acetonitrile 75-05-8

SARA 302 Components :

SARA 313 Components :
: Acetonitrile 75-05-8

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Chronic Health Hazard

**CERCLA Reportable
Quantity** : 5005 lbs

SAFETY DATA SHEET

Honeywell

LC407-2.5 (0.1% TFA IN ACETONITRILE)

000000011215

Version 1.4

Revision Date 04/08/2014

Print Date 02/25/2016

California Prop. 65 : WARNING! This product contains a chemical known to the State of California to cause cancer.
Acrylonitrile 107-13-1

Massachusetts RTK : Acetonitrile 75-05-8

New Jersey RTK : Acetonitrile 75-05-8

Pennsylvania RTK : Acetonitrile 75-05-8

WHMIS Classification : B2: Flammable liquid
D1A: Very Toxic Material Causing Immediate and Serious Toxic Effects
D2B: Toxic Material Causing Other Toxic Effects
This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 2*	2
Flammability	: 3	3
Physical Hazard	: 0	
Instability	:	0

* - Chronic health hazard

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe

LC407-2.5 (0.1% TFA IN ACETONITRILE)**000000011215**

Version 1.4

Revision Date 04/08/2014

Print Date 02/25/2016

handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 07/01/2011

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group