Printing date 02/06/2014 Reviewed on 02/06/2014

1 Identification

· Product identifier

· Trade name: Methyl Isobutyl Ketone (4-Methyl-2-pentanone), Laboratory Grade 99%

· Article number: M5700

• CAS Number: 108-10-1 • EC number: 203-550-1

· Index number: 606-004-00-4

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc.

Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA

800-256-2586

· Information department:

Product safety department Technical Coordinator

Sherman Nelson sherman@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard statements

Highly flammable liquid and vapor.

Harmful if inhaled.

(Contd. on page 2)

Printing date 02/06/2014 Reviewed on 02/06/2014

Trade name: Methyl Isobutyl Ketone (4-Methyl-2-pentanone), Laboratory Grade 99%

(Contd. of page 1)

Causes serious eye irritation.

May cause respiratory irritation.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description

108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

- · Identification number(s)
- · EC number: 203-550-1
- · Index number: 606-004-00-4

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 02/06/2014 Reviewed on 02/06/2014

Trade name: Methyl Isobutyl Ketone (4-Methyl-2-pentanone), Laboratory Grade 99%

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

Printing date 02/06/2014 Reviewed on 02/06/2014

Trade name: Methyl Isobutyl Ketone (4-Methyl-2-pentanone), Laboratory Grade 99%

(Contd. of page 3)

· Control parameters

· Components with limit values that require monitoring at the workplace:

108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

PEL Long-term value: 410 mg/m³, 100 ppm

REL Short-term value: 300 mg/m³, 75 ppm

Long-term value: 205 mg/m³, 50 ppm

TLV Short-term value: 307 mg/m³, 75 ppm

Long-term value: 82 mg/m³, 20 ppm

· Ingredients with biological limit values:

108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

BEI 1 mg/L

BEI

Medium: urine Time: end of shift Parameter: MIBK

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

USA

Printing date 02/06/2014 Reviewed on 02/06/2014

Trade name: Methyl Isobutyl Ketone (4-Methyl-2-pentanone), Laboratory Grade 99%

(Contd. of page 4)

| Information on basic physical and of General Information | chemical properties |
|--|--|
| Appearance: | |
| Form: | Liquid |
| Color: | Colorless |
| Odor: | Light Ketonic |
| Odour threshold: | Not determined. |
| pH-value: | Not determined. |
| Change in condition | |
| Melting point/Melting range: | -83.5 °C (-118 °F) |
| Boiling point/Boiling range: | 114-117 °C (237-243 °F) |
| Flash point: | 14 °C (57 °F) |
| Flammability (solid, gaseous): | Not applicable. |
| Ignition temperature: | 460 °C (860 °F) |
| Decomposition temperature: | Not determined. |
| Auto igniting: | Not determined. |
| Danger of explosion: | Product is not explosive. However, formation of explosive air/vap mixtures are possible. |
| Explosion limits: | |
| Lower: | 1.7 Vol % |
| Upper: | 9 Vol % |
| Vapor pressure at 20 °C (68 °F): | 8 hPa (6 mm Hg) |
| Density at 20 °C (68 °F): | 0.8008 g/cm³ (6.683 lbs/gal) |
| Relative density | Not determined. |
| Vapour density | Not determined. |
| Evaporation rate | Not determined. |
| Solubility in / Miscibility with | |
| Water at 20 °C (68 °F): | 19 g/l |
| Partition coefficient (n-octanol/wate | er): Not determined. |
| Viscosity: | |
| Dynamic at 20 °C (68 °F): | 0.59 mPas |
| Kinematic: | Not determined. |
| Other information | No further relevant information available. |

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 6)

Printing date 02/06/2014 Reviewed on 02/06/2014

Trade name: Methyl Isobutyl Ketone (4-Methyl-2-pentanone), Laboratory Grade 99%

(Contd. of page 5)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

| Oral | LD50 | 2080 mg/kg (rat) |
|------------|----------|---------------------|
| | LD50 | 16000 mg/kg (rab) |
| Inhalative | LC50/4 h | 8.3-16.6 mg/l (rat) |

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer) Substance is not listed.
- · NTP (National Toxicology Program) Substance is not listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Assessment by list): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

USA

Printing date 02/06/2014 Reviewed on 02/06/2014

Trade name: Methyl Isobutyl Ketone (4-Methyl-2-pentanone), Laboratory Grade 99%

(Contd. of page 6)

| UN-Number | |
|--|--|
| DOT, IMDG, IATA | UN1245 |
| UN proper shipping name | |
| DOT | Methyl isobutyl ketone |
| IMDG, IATA | METHYL ISOBUTYL KETONE |
| Transport hazard class(es) | |
| DOT | |
| | |
| FLAMMABLE LIQUID | |
| 3 | |
| Class | 3 Flammable liquids. |
| Label | 3 |
| IMDG, IATA | |
| | |
| 3 | |
| Class | 3 Flammable liquids. |
| | 3 Flammable liquids. 3 |
| Label Packing group | 3 |
| Label Packing group | |
| Label Packing group DOT, IMDG, IATA Environmental hazards: | 3 II |
| Label Packing group DOT, IMDG, IATA Environmental hazards: | 3 |
| Class Label Packing group DOT, IMDG, IATA Environmental hazards: Marine pollutant: Special precautions for user | 3 II No Warning: Flammable liquids |
| Label Packing group DOT, IMDG, IATA Environmental hazards: Marine pollutant: Special precautions for user Danger code (Kemler): | 3 II No Warning: Flammable liquids 33 |
| Label Packing group DOT, IMDG, IATA Environmental hazards: Marine pollutant: Special precautions for user Danger code (Kemler): | 3 II No Warning: Flammable liquids |
| Label Packing group DOT, IMDG, IATA Environmental hazards: Marine pollutant: Special precautions for user Danger code (Kemler): EMS Number: Transport in bulk according to Annex | II No Warning: Flammable liquids 33 F-E,S-D II of |
| Label Packing group DOT, IMDG, IATA Environmental hazards: Marine pollutant: Special precautions for user Danger code (Kemler): EMS Number: | II No Warning: Flammable liquids 33 F-E,S-D |

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances): Substance is not listed.
- · Section 313 (Specific toxic chemical listings): Substance is listed.
- · TSCA (Toxic Substances Control Act): Substance is listed.
- · Proposition 65
- · Chemicals known to cause cancer: Substance is listed.
- · Chemicals known to cause reproductive toxicity for females: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for males: Substance is not listed.
- · Chemicals known to cause developmental toxicity: Substance is not listed.

(Contd. on page 8)

Printing date 02/06/2014 Reviewed on 02/06/2014

Trade name: Methyl Isobutyl Ketone (4-Methyl-2-pentanone), Laboratory Grade 99%

(Contd. of page 7)

Ι

· Carcinogenic categories

· EPA (Environmental Protection Agency)

108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

- · TLV (Threshold Limit Value established by ACGIH) Substance is not listed.
- · NIOSH-Ca (National Institute for Occupational Safety and Health) Substance is not listed.
- · OSHA-Ca (Occupational Safety & Health Administration) Substance is not listed.
- · GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard statements

Highly flammable liquid and vapor.

Harmful if inhaled.

Causes serious eye irritation.

May cause respiratory irritation.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Environment protection department.
- · Contact: Mr. Nelson
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Acute Tox. 4: Acute toxicity, Hazard Category 4

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

USA