

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Revision Date 04/03/2014

Version 1. 1

SECTION 1.Identification

Product identifier

Product number TX0279

Product name Tetrahydrofuran Unstabilized For UV Spectrophotometry Use

OmniSolv®

CAS-No. 109-99-9

Relevant identified uses of the substance or mixture and uses advised against

Identified uses Reagent for analysis

Details of the supplier of the safety data sheet

Company EMD Millipore Corporation | 290 Concord Road, Billerica, MA 01821,

United States of America | General Inquiries: +1-978-715-4321 | Monday to Friday, 9:00 AM to 4:00 PM Eastern Time (GMT-5)

Emergency telephone 800-424-9300 CHEMTREC (USA)

+1-703-527-3887 CHEMTREC (International)

24 Hours/day; 7 Days/week

SECTION 2. Hazards identification

GHS Classification

Flammable liquid, Category 2, H225 Carcinogenicity, Category 2, H351 Eye irritation, Category 2, H319

Specific target organ systemic toxicity - single exposure, Category 3, Respiratory system, H335

For the full text of the H-Statements mentioned in this Section, see Section 16.

GHS-Labeling

Hazard pictograms







Signal Word
Danger

Hazard Statements

H225 Highly flammable liquid and vapor.

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number TX0279 Version 1.1

Product name Tetrahydrofuran Unstabilized For UV Spectrophotometry Use OmniSolv®

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

Precautionary Statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

OSHA Hazards

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200). This information is based on 29 CFR 1910.1200 criteria prior to adoption of the GHS and may deviate from the GHS information.

Other hazards

None known.

SECTION 3. Composition/information on ingredients

Formula C_4H_8O (Hill) Molar mass 72.11 g/mol

Hazardous ingredients

Chemical Name (Concentration)

CAS-No.

tetrahydrofuran (>= 90 % - <= 100 %)

109-99-9

Exact percentages are being withheld as a trade secret.

SECTION 4. First aid measures

Description of first-aid measures

Inhalation

After inhalation: fresh air. Call in physician.

Skin contact

After skin contact: wash off with plenty of water. Remove contaminated clothing. Consult a

physician.

Eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist.

Ingestion

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

Never give anything by mouth to an unconscious person.

Most important symptoms and effects, both acute and delayed

irritant effects, Cough, Shortness of breath, narcosis, drowziness

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number TX0279 Version 1.1

Product name Tetrahydrofuran Unstabilized For UV Spectrophotometry Use OmniSolv®

Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

Dry powder, Foam, Carbon dioxide (CO2)

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

Special hazards arising from the substance or mixture

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at ambient temperatures.

Pay attention to flashback.

Development of hazardous combustion gases or vapors possible in the event of fire.

Advice for firefighters

Special protective equipment for fire-fighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Avoid substance contact. Do not breathe vapors, aerosols. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert.

Advice for emergency responders: Protective equipment see section 8.

Environmental precautions

Do not empty into drains. Risk of explosion.

Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills.

Observe possible material restrictions (see sections 7 and 10).

Take up with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

SECTION 7. Handling and storage

Precautions for safe handling

Observe label precautions.

Work under hood. Do not inhale substance/mixture. Avoid generation of vapors/aerosols.

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number Version 1.1

Product name Tetrahydrofuran Unstabilized For UV Spectrophotometry Use OmniSolv®

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Protected from light.

No declaration

SECTION 8. Exposure controls/personal protection

Exposure limit(s)

NIOSH/GUIDE

Ingredients

Threshold **Basis** Value Remarks

limits

tetrahydrofuran 109-99-9

ACGIH Time Weighted Average 50 ppm

(TWA):

Skin designation: Can be absorbed through the skin.

Short Term Exposure

Limit (STEL):

Recommended 200 ppm exposure limit (REL):

590 mg/m³

Short Term Exposure 250 ppm 735 mg/m³ Limit (STEL):

OSHA_TRANS PEL: 200 ppm

590 mg/m³

590 mg/m³

100 ppm

Short Term Exposure 250 ppm Z1A

(TWA):

Limit (STEL): 735 mg/m³ Time Weighted Average 200 ppm

Engineering measures

Technical measures and appropriate working operations should be given priority over the use of personal protective equipment.

Individual protection measures

Protective clothing should be selected specifically for the workplace, depending on concentration and quantity of the hazardous substances handled. The chemical resistance of the protective equipment should be inquired at the respective supplier.

Hygiene measures

Immediately change contaminated clothing. Apply skin- protective barrier cream. Wash hands and face after working with substance.

Eye/face protection

Safety glasses

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number TX0279 Version 1.1

Product name Tetrahydrofuran Unstabilized For UV Spectrophotometry Use OmniSolv®

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Other protective equipment:

Flame retardant antistatic protective clothing

Respiratory protection

required when vapors/aerosols are generated.

Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

SECTION 9. Physical and chemical properties

Physical state liquid

Color colorless

Odor ether-like

Odor Threshold 2.0 - 59.0 ppm

pH 7-8

at 200 g/l 68 °F (20 °C)

Melting point -108.5 °C

Boiling point/boiling range 149 - 151 °F (65 - 66 °C)

at 1,013 hPa

Flash point -4 °F (-20 °C)

Method: c.c.

Evaporation rate No information available.

Flammability (solid, gas) No information available.

Lower explosion limit 1.5 %(V)

Upper explosion limit 12.4 %(V)

Vapor pressure 173 hPa

at 68 °F (20 °C)

Relative vapor density 2.5

Density 0.89 g/cm³

at 68 °F (20 °C)

Relative density No information available.

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number TX0279 Version 1. 1

Product name Tetrahydrofuran Unstabilized For UV Spectrophotometry Use OmniSolv®

Water solubility at 68 °F (20 °C)

soluble

Partition coefficient: n-

octanol/water

log Pow: 0.45 (25 °C) OECD Test Guideline 107

Bioaccumulation is not expected.

Autoignition temperature No information available.

Decomposition temperature No information available.

Viscosity, dynamic 0.47 mPa.s

at 68 °F (20 °C)

Explosive properties Not classified as explosive.

Oxidizing properties none

Ignition temperature 419 °F (215 °C)

SECTION 10. Stability and reactivity

Reactivity

Vapors may form explosive mixture with air.

Chemical stability

Sensitivity to light

Sensitive to air.

Possibility of hazardous reactions

A risk of explosion and/or of toxic gas formation exists with the following substances:

alkali hydroxides, hydrides, Oxidizing agents, Bromine

Oxygen

Conditions to avoid

Warming.

Incompatible materials

rubber, various plastics, Tin

Hazardous decomposition products

Peroxides

SECTION 11. Toxicological information

Information on toxicological effects

Likely route of exposure

Inhalation, Eye contact, Skin contact

Target Organs

Eyes

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number TX0279 Version 1.1

Product name Tetrahydrofuran Unstabilized For UV Spectrophotometry Use OmniSolv®

Respiratory system Central nervous system

Acute oral toxicity

LD50 rat: 1,650 mg/kg (RTECS) (Regulation (EC) No 1272/2008, Annex VI)

Symptoms: Irritation of mucous membranes

Acute inhalation toxicity

LC50 rat: 53.9 mg/l; 4 h (IUCLID) Irritating to respiratory system.

Symptoms: mucosal irritations, Cough, Shortness of breath, Possible damages:, damage of

respiratory tract

Acute dermal toxicity

absorption

Skin irritation

rabbit

Result: Irritations

(IUCLID) (Regulation (EC) No 1272/2008, Annex VI)

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Eye irritation

rabbit

Result: Eye irritation

(IUCLID)

Causes serious eye irritation.

Sensitization

Sensitization test: guinea pig

Result: negative

(IUCLID)

Human experience

Result: negative

(IUCLID)

Genotoxicity in vitro

Ames test

Result: negative

(IUCLID)

Reproductive toxicity

No impairment of reproductive performance suspected. (Lit.)

CMR effects

Carcinogenicity:

Suspected of causing cancer.

Specific target organ systemic toxicity - single exposure

Target Organs: Respiratory system May cause respiratory irritation.

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number TX0279 Version 1.1

Product name Tetrahydrofuran Unstabilized For UV Spectrophotometry Use OmniSolv®

Specific target organ systemic toxicity - repeated exposure

The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration hazard

Regarding the available data the classification criteria are not fulfilled.

Carcinogenicity

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

ACGIH Confirmed animal carcinogen with unknown relevance to

humans.

tetrahydrofuran 109-99-9

Further information

In high doses:

drowziness, narcosis

Handle in accordance with good industrial hygiene and safety practice.

SECTION 12. Ecological information

Ecotoxicity

Toxicity to fish

LC50 Pimephales promelas (fathead minnow): 2,160 mg/l; 96 h (in soft water) (IUCLID)

Toxicity to daphnia and other aquatic invertebrates

EC50 Daphnia magna (Water flea): 382 mg/l; 24 h (IUCLID)

Toxicity to algae

IC5 Scenedesmus quadricauda (Green algae): 3,700 mg/l; 8 d (maximum permissible toxic concentration) (IUCLID)

Toxicity to bacteria

EC5 Pseudomonas putida: 580 mg/l; 16 h (maximum permissible toxic concentration) (IUCLID)

Persistence and degradability

Biodegradability

39 %; 28 d

OECD Test Guideline 301D Not readily biodegradable.

Bioaccumulative potential

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number TX0279 Version 1.1

Product name Tetrahydrofuran Unstabilized For UV Spectrophotometry Use OmniSolv®

Partition coefficient: n-octanol/water

log Pow: 0.45 (25 °C) OECD Test Guideline 107 Bioaccumulation is not expected.

Mobility in soil

No information available.

Additional ecological information

Discharge into the environment must be avoided.

SECTION 13. Disposal considerations

The information presented only applies to the material as supplied. The identification based on characteristic(s) or listing may not apply if the material has been used or otherwise contaminated. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable regulations. Disposal should be in accordance with applicable regional, national and local laws and regulations.

SECTION 14. Transport information

Land transport (DOT)

UN number UN 2056

Proper shipping name TETRAHYDROFURAN

Class 3
Packing group II
Environmentally hazardous ---

Air transport (IATA)

UN number UN 2056

Proper shipping name TETRAHYDROFURAN

Class 3
Packing group II
Environmentally hazardous --Special precautions for user no

Sea transport (IMDG)

UN number UN 2056

Proper shipping name TETRAHYDROFURAN

Class 3
Packing group II
Environmentally hazardous -Special precautions for user
EmS yes
F-E S-D

SECTION 15. Regulatory information

United States of America

OSHA Hazards

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number TX0279 Version 1.1

Product name Tetrahydrofuran Unstabilized For UV Spectrophotometry Use OmniSolv®

Flammable Liquid

Harmful if swallowed.

Eye irritant

Respiratory irritant

Carcinogen

Target organ effects

This information is based on 29 CFR 1910.1200 criteria prior to adoption of the GHS, and may deviate from the GHS information on the label and in section 2.

SARA 311/312 Hazards

Fire Hazard

Acute Health Hazard

Chronic Health Hazard

SARA 313

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

SARA 302

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III. Section 302.

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311,

Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311,

Table 117.3.

DEA List I

Not listed

DEA List II

Not listed

US State Regulations

Massachusetts Right To Know

Ingredients

tetrahydrofuran

Pennsylvania Right To Know

Ingredients

tetrahydrofuran

New Jersey Right To Know

Ingredients

tetrahydrofuran

California Prop 65 Components

This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

according to the (US) Hazard Communication Standard (29 CFR 1910.1200)

Product number TX0279 Version 1.1

Product name Tetrahydrofuran Unstabilized For UV Spectrophotometry Use OmniSolv®

Notification status

TSCA: All components of the product are listed in the TSCA-inventory.

DSL: All components of this product are on the Canadian DSL.

SECTION 16. Other information

Training advice

Provide adequate information, instruction and training for operators.

Full text of H-Statements referred to under sections 2 and 3.

H225	Highly flammable liquid and vapor.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.

Key or legend to abbreviations and acronyms used in the safety data sheet

Used abbreviations and acronyms can be looked up at www.wikipedia.org.

Revision Date 04/03/2014

The information contained herein is based on the present state of our knowledge. It characterizes the product with regard to appropriate safety precautions. It does not represent a warranty of any product properties and we assume no liability for any loss or injury which may result from the use of this information. Users should conduct their own investigations to determine the suitability of the information.

All rights reserved. Millipore and the "M" Mark are registered trademarks of Merck KGaA, Darmstadt, Germany.