

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : Diphenylamine, 1% in Sulfuric Acid

Product code : LC13650

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : For laboratory and manufacturing use only.

1.3. Details of the supplier of the safety data sheet

LabChem Inc

Jackson's Pointe Commerce Park Building 1000, 1010 Jackson's Pointe Court

Zelienople, PA 16063 - USA T 412-826-5230 - F 724-473-0647 info@labchem.com - www.labchem.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 or 011-703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

 Skin Corr. 1B
 H314

 Eye Dam. 1
 H318

 STOT RE 2
 H373

 Aquatic Acute 2
 H401

 Aquatic Chronic 2
 H411

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)







GHS05

GHS08

GHS09

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H314 - Causes severe skin burns and eye damage

H373 - May cause damage to organs (liver, kidneys, blood) through prolonged or repeated

exposure

H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) : P260 - Do not breathe mist, vapors, spray

P264 - Wash exposed skin thoroughly after handling

P273 - Avoid release to the environment

P280 - Wear protective gloves, protective clothing, eye protection, face protection P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing P310 - Immediately call a poison center/doctor P363 - Wash contaminated clothing before reuse

P391 - Collect spillage P405 - Store locked up

P501 - Dispose of contents/container to comply with local, state and federal regulations

2.3. Other hazards

Other hazards not contributing to the : None under normal conditions.

01/07/2015 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

classification

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % | Classification (GHS-US) |
|---------------|--------------------|-------|--|
| Sulfuric Acid | (CAS No) 7664-93-9 | 95.04 | Skin Corr. 1A, H314 Eye Dam. 1, H318 |
| Water | (CAS No) 7732-18-5 | 3.96 | Not classified |
| Diphenylamine | (CAS No) 122-39-4 | 1 | Acute Tox. 4 (Oral), H302 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a

poison center or doctor/physician.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Immediately call a poison center or doctor/physician.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes severe skin burns and eye damage. Causes damage to organs.

Symptoms/injuries after inhalation : Possible inflammation of the respiratory tract.

Symptoms/injuries after skin contact : Caustic burns/corrosion of the skin.
Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : Burns to the gastric/intestinal mucosa. Nausea. Vomiting. Methemoglobinemia.

Chronic symptoms : Decreased renal function. Enlargement/affection of the liver.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Reactivity : Thermal decomposition generates : Corrosive vapors.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Protective clothing. Face-shield. Gloves.

Emergency procedures : Evacuate unnecessary personnel.

01/07/2015 EN (English US) 2/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Provide good ventilation in process area to prevent formation

of vapor. Do not breathe mist, vapors, spray.

Hygiene measures : Wash exposed skin thoroughly after handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

Storage conditions : Keep container closed when not in use. Protect from sunlight.

Incompatible products : Strong oxidizers. Strong bases.
Incompatible materials : Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Diphenylamine, 1% in Sulfuric Acid | | | |
|------------------------------------|--------------------------|-----------|--|
| ACGIH | Not applicable | | |
| OSHA | Not applicable | | |
| Diphenylamine (122-39-4) | Diphenylamine (122-39-4) | | |
| ACGIH | ACGIH TWA (mg/m³) | 10 mg/m³ | |
| OSHA | Not applicable | | |
| Sulfuric Acid (7664-93-9) | | | |
| ACGIH | ACGIH TWA (mg/m³) | 0.2 mg/m³ | |
| OSHA | OSHA PEL (TWA) (mg/m³) | 1 mg/m³ | |
| Water (7732-18-5) | | | |
| ACGIH | Not applicable | | |
| OSHA | Not applicable | | |

8.2. Exposure controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate

vicinity of any potential exposure. Ensure adequate ventilation.

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or face shield.
Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear appropriate mask.

Other information : Do not eat, drink or smoke during use.

01/07/2015 EN (English US) 3/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Colorless
Odor : None.

Odor threshold : No data available No data available Relative evaporation rate (butyl acetate=1) : No data available : No data available Melting point Freezing point No data available Boiling point : No data available : No data available Flash point Auto-ignition temperature : No data available Decomposition temperature : No data available Flammability (solid, gas) No data available : No data available Vapor pressure Relative vapor density at 20 °C No data available Relative density : No data available Specific gravity / density 1.84 g/ml

Solubility : Soluble in water.

Water: Solubility in water of component(s) of the mixture :

Sulfuric Acid:
No data available
No data available
No data available
No data available

Explosive properties : No data available
Oxidizing properties : No data available
Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Viscosity, kinematic Viscosity, dynamic

Log Pow

Log Kow

Thermal decomposition generates: Corrosive vapors.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong oxidizers. Strong bases.

10.6. Hazardous decomposition products

Sulfur compounds. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| Diphenylamine (122-39-4) | |
|--------------------------|------------|
| LD50 oral rat | 1120 mg/kg |

01/07/2015 EN (English US) 4/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Diphenylamine (122-39-4) | | |
|--|--|--|
| ATE US (oral) | 1120.000 mg/kg body weight | |
| Sulfuric Acid (7664-93-9) | | |
| LD50 oral rat | 2140 mg/kg body weight (Rat; Experimental value) | |
| Water (7732-18-5) | | |
| LD50 oral rat | ≥ 90000 mg/kg | |
| ATE US (oral) | 90000.000 mg/kg body weight | |
| Skin corrosion/irritation | : Causes severe skin burns and eye damage. | |
| Serious eye damage/irritation | : Causes serious eye damage. | |
| Respiratory or skin sensitization | : Not classified | |
| Germ cell mutagenicity | : Not classified | |
| Carcinogenicity | : Not classified | |
| Diphenylamine, 1% in Sulfuric Acid | | |
| Additional information | Strong inorganic acid mists containing sulfuric acid are carcinogenic to humans | |
| Sulfuric Acid (7664-93-9) | | |
| Additional information | Strong inorganic acid mists containing sulfuric acid are carcinogenic to humans | |
| IARC group | 1 - Carcinogenic to humans | |
| National Toxicology Program (NTP) Status | 2 - Known Human Carcinogens | |
| Reproductive toxicity | : Not classified | |
| Specific target organ toxicity (single exposure) | : Not classified | |
| Specific target organ toxicity (repeated exposure) | : May cause damage to organs (liver, kidneys, blood) through prolonged or repeated exposure. | |
| Aspiration hazard | : Not classified | |
| Detential Advares human health offeets and | . Decad on available data the algorification criteria are not mot | |

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation : Possible inflammation of the respiratory tract. Symptoms/injuries after skin contact : Caustic burns/corrosion of the skin.

Symptoms/injuries after skin contact : Caustic burns/corrosion of the skin Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : Burns to the gastric/intestinal mucosa. Nausea. Vomiting. Methemoglobinemia.

Chronic symptoms : Decreased renal function. Enlargement/affection of the liver.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

| Diphenylamine (122-39-4) | | |
|---|--|--|
| LC50 fish 1 | 3.79 mg/l 96 hr., Pimephales promelas | |
| EC50 Daphnia 1 | 0.27 - 0.36 48 hr., Daphnia magna | |
| EC50 other aquatic organisms 1 | 0.048 mg/l 72 hr., Desmodesmus subspicatus | |
| Sulfuric Acid (7664-93-9) | | |
| LC50 fish 1 | 42 mg/l (96 h; Gambusia affinis) | |
| EC50 Daphnia 1 | 29 mg/l (24 h; Daphnia magna) | |
| LC50 fish 2 | 49 mg/l (48 h; Lepomis macrochirus) | |
| TLM fish 1 | 42 mg/l (96 h; Gambusia affinis) | |
| Threshold limit other aquatic organisms 1 | 6900 mg/l (24 h; Pseudomonas fluorescens) | |

12.2. Persistence and degradability

| Diphenylamine, 1% in Sulfuric Acid | | |
|------------------------------------|---|--|
| Persistence and degradability | May cause long-term adverse effects in the environment. | |
| Diphenylamine (122-39-4) | | |
| Persistence and degradability | Not readily biodegradable in water. | |
| Sulfuric Acid (7664-93-9) | | |
| Persistence and degradability | Biodegradability: not applicable. | |
| 04/07/0045 | EN (Elist UC) | |

01/07/2015 EN (English US) 5/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Sulfuric Acid (7664-93-9) | |
|---------------------------------|------------------|
| Biochemical oxygen demand (BOD) | Not applicable |
| Chemical oxygen demand (COD) | Not applicable |
| ThOD | Not applicable |
| BOD (% of ThOD) | Not applicable |
| Water (7732-18-5) | |
| Persistence and degradability | Not established. |

12.3. Bioaccumulative potential

| Diphenylamine, 1% in Sulfuric Acid | | |
|-------------------------------------|--|--|
| Bioaccumulative potential | Not established. | |
| Diphenylamine (122-39-4) | | |
| Bioconcentration factor (BCF REACH) | 253 | |
| Log Pow | 3.5 | |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). | |
| Sulfuric Acid (7664-93-9) | | |
| Log Pow | -2.20 (Estimated value) | |
| Bioaccumulative potential | Bioaccumulation: not applicable. | |
| Water (7732-18-5) | | |
| Bioaccumulative potential | Not established. | |

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer

Effect on the global warming : No known ecological damage caused by this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to comply with local, state and federal regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1830 Sulfuric acid, 8, II

UN-No.(DOT) : UN1830
Proper Shipping Name (DOT) : Sulfuric acid

Department of Transportation (DOT) Hazard

Classes

: 8 - Class 8 - Corrosive material 49 CFR 173.136

Hazard labels (DOT) : 8 - Corrosive



Packing group (DOT) : II - Medium Danger

01/07/2015 EN (English US) 6/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

: A3 - For combination packaging, if glass inner packaging (including ampoules) are used, they must be packed with absorbent material in tightly closed metal receptacles before packing in outer packaging.

A7 - Steel packaging must be corrosion-resistant or have protection against corrosion. B3 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks and DOT 57 portable tanks are not authorized.

B83 - Bottom outlets are prohibited on tank car tanks transporting sulfuric acid in concentrations over 65.25 percent.

B84 - Packaging must be protected with non-metallic linings impervious to the lading or have a suitable corrosion allowance for sulfuric acid or spent sulfuric acid in concentration up to 65.25 percent.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

N34 - Aluminum construction materials are not authorized for any part of a packaging which is normally in contact with the hazardous material.

T8 - 4 178.274(d)(2) Normal..... Prohibited

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP12 - This material is considered highly corrosive to steel.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154 DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242 DOT Quantity Limitations Passenger aircraft/rail : 1 L (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

: C - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel. **DOT Vessel Stowage Location**

DOT Vessel Stowage Other : 14 - For metal drums, stowage permitted under deck on cargo vessels

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

UN-No. (IMDG) : 1830

Proper Shipping Name (IMDG) : SULPHURIC ACID Class (IMDG) : 8 - Corrosive substances

Packing group (IMDG) : II - substances presenting medium danger

Air transport

UN-No.(IATA) : 1830

Proper Shipping Name (IATA) : Sulphuric acid Class (IATA) : 8 - Corrosives Packing group (IATA) : II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

| Diphenylamine, 1% in Sulfuric Acid | |
|-------------------------------------|---------------------------------|
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard |
| | Delayed (chronic) health hazard |

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

01/07/2015 EN (English US) 7/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Diphenylamine (122-39-4) | | |
|--|--|--|
| Listed on United States SARA Section 313 | | |
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard Delayed (chronic) health hazard | |
| Sulfuric Acid (7664-93-9) | | |
| Listed on United States SARA Section 313 | | |
| RQ (Reportable quantity, section 304 of EPA's List of Lists) | 1000 lb | |
| SARA Section 302 Threshold Planning Quantity (TPQ) | 1000 lb | |
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard | |

15.2. International regulations

CANADA

| Diphenylamine, 1% in Sulfuric Acid | |
|------------------------------------|---|
| WHMIS Classification | Class E - Corrosive Material |
| | Class D Division 2 Subdivision B - Toxic material causing other toxic effects |

| Diphenylamine (122-39-4) | | |
|--|---|--|
| Listed on the Canadian DSL (Domestic Sustant | ces List) | |
| WHMIS Classification | Class D Division 2 Subdivision B - Toxic material causing other toxic effects | |
| Sulfuric Acid (7664-93-9) | | |
| WHMIS Classification | Class E - Corrosive Material | |
| Water (7732-18-5) | | |
| Listed on the Canadian DSL (Domestic Sustances List) | | |
| WHMIS Classification | Uncontrolled product according to WHMIS classification criteria | |

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

| Dinhenylam | ino /122 | 20.4\ |
|------------|----------|-------|
| | | |

Listed on the Canadian IDL (Ingredient Disclosure List)

Sulfuric Acid (7664-93-9)

Listed on IARC (International Agency for Research on Cancer) Listed as carcinogen on NTP (National Toxicology Program)

Water (7732-18-5)

Not listed on the Canadian IDL (Ingredient Disclosure List)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Other information : None.

01/07/2015 EN (English US) 8/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases: see section 16:

| Acute Tox. 4 (Oral) | Acute toxicity (oral) Category 4 | |
|---------------------|---|--|
| Aquatic Acute 1 | Hazardous to the aquatic environment - Acute Hazard Category 1 | |
| Aquatic Acute 2 | Hazardous to the aquatic environment - Acute Hazard Category 2 | |
| Aquatic Chronic 1 | Hazardous to the aquatic environment - Chronic Hazard Category 1 | |
| Aquatic Chronic 2 | Hazardous to the aquatic environment - Chronic Hazard Category 2 | |
| Eye Dam. 1 | Serious eye damage/eye irritation Category 1 | |
| Skin Corr. 1A | Skin corrosion/irritation Category 1A | |
| Skin Corr. 1B | Skin corrosion/irritation Category 1B | |
| STOT RE 2 | Specific target organ toxicity (repeated exposure) Category 2 | |
| H302 | Harmful if swallowed | |
| H314 | Causes severe skin burns and eye damage | |
| H318 | Causes serious eye damage | |
| H373 | May cause damage to organs through prolonged or repeated exposure | |
| H400 | Very toxic to aquatic life | |
| H401 | Toxic to aquatic life | |
| H410 | Very toxic to aquatic life with long lasting effects | |
| H411 | Toxic to aquatic life with long lasting effects | |
| | | |

NFPA health hazard

: 4 - Very short exposure could cause death or serious residual injury even though prompt medical attention was

given.

NFPA fire hazard

: 0 - Materials that will not burn.

NFPA reactivity

: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with

some release of energy, but not violently.

NFPA specific hazard

: W - Unusual reactivity with water. This indicates a potential hazard using water to fight a fire involving this material. When a compound is both water-reactive and an oxidizer, the W/bar symbol should go in this quadrant and the OX warning is placed immediately below the NFPA diamond.



HMIS III Rating

Health

: 4 Severe Hazard - Life-threatening, major or permanent damage may result from single or

repeated overexposures

Flammability : 0 Minimal Hazard
Physical : 1 Slight Hazard
Personal Protection : D

SDS US (GHS HazCom 2012)

Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and LabChem Inc assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.

01/07/2015 EN (English US) 9/9