

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : Selenium AA Standard, 1000 ppm (1mL = 1mg Se)

Product code : LC22370

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : For laboratory and manufacturing use only.

1.3. Details of the supplier of the safety data sheet

LabChem Inc

Jackson's Pointe Commerce Park Building 1000, 1010 Jackson's Pointe Court

Zelienople, PA 16063 - USA T 412-826-5230 - F 724-473-0647 info@labchem.com - www.labchem.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 or 011-703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Met. Corr. 1 H290 Skin Corr. 1B H314 Eye Dam. 1 H318

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS05

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H290 - May be corrosive to metals

H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS-US) : P234 - Keep only in original container

P260 - Do not breathe mist

P264 - Wash exposed skin thoroughly after handling

P280 - Wear protective gloves, protective clothing, eye protection, face protection P301+P330+P331 - IF SWALLOWED: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing P310 - Immediately call a poison center/doctor P363 - Wash contaminated clothing before reuse P390 - Absorb spillage to prevent material damage

P405 - Store locked up

P406 - Store in corrosive resistant container with a resistant inner liner

P501 - Dispose of contents/container to comply with local, state and federal regulations

2.3. Other hazards

Other hazards not contributing to the

classification

: None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

04/30/2015 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Water	(CAS No) 7732-18-5	95.9	Not classified
Nitric Acid	(CAS No) 7697-37-2	4	Ox. Liq. 3, H272 Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318
Selenium	(CAS No) 7782-49-2	0.1	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Inhalation), H331 STOT RE 2, H373 Aquatic Chronic 4, H413

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible).

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately

call a poison center or doctor/physician.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Immediately call a poison center or doctor/physician.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Immediately call a poison center or doctor/physician.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes severe skin burns and eye damage.

Symptoms/injuries after inhalation : Irritation of the respiratory tract.

Symptoms/injuries after skin contact : Burns. Yellow skin.

Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : Burns. Central nervous system depression.

Chronic symptoms : Central nervous system depression. Affection/discolouration of the teeth. Enlargement/affection

of the liver. Emotional instability.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Reactivity : Thermal decomposition generates : Corrosive vapors.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Protective clothing. Gloves. Face-shield.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

04/30/2015 EN (English US) 2/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Absorb spillage to prevent material damage.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: May be corrosive to metals.

Precautions for safe handling

 Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation

of vapor. Do not breathe mist.

Hygiene measures : Wash exposed skin thoroughly after handling. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Comply with applicable regulations.

Storage conditions

: Keep only in the original container in a cool, well ventilated place away from : incompatible

materials, Direct sunlight. Keep container closed when not in use.

Incompatible products : Strong bases. Strong oxidizers.
Incompatible materials : Sources of ignition. Direct sunlight.

Country of Indiana.

Packaging materials : Store in corrosive resistant/... container with a resistant inner liner.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

Selenium AA Standard, 1000 ppm (1mL = 1mg Se)

8.1. Control parameters

ACGIH	Not applicable	
OSHA	Not applicable	
Selenium (7782-49-2)		
ACGIH	ACGIH TWA (mg/m³)	0.2 mg/m³
OSHA	OSHA PEL (TWA) (mg/m³)	0.2 mg/m³

Nitric Acid, 70% w/w (7697-3	Nitric Acid, 70% w/w (7697-37-2)		
ACGIH	ACGIH TWA (ppm)	2 ppm	
OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m³	
OSHA	OSHA PEL (TWA) (ppm)	2 ppm	

Water (7732-18-5)	
ACGIH	Not applicable
OSHA	Not applicable

8.2. Exposure controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate

vicinity of any potential exposure. Ensure adequate ventilation.

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or face shield.
Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear appropriate mask.

Other information : Do not eat, drink or smoke during use.

04/30/2015 EN (English US) 3/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : Colorless

Odor : characteristic

Odor threshold : No data available

pH : No data available

Melting point : No data available

Freezing point : No data available

Boiling point : 105 °C

Flash point : No data available Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : No data available **Explosion limits** : No data available No data available Explosive properties Oxidizing properties : No data available Vapor pressure No data available Relative density No data available Relative vapor density at 20 °C : No data available Solubility Miscible with water.

Water: Solubility in water of component(s) of the mixture :

· Nitric Acid, 70% w/w:

Log Pow : No data available
Log Kow : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Viscosity : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates: Corrosive vapors.

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong oxidizers. Strong bases. metals. May be corrosive to metals.

10.6. Hazardous decomposition products

Nitrogen oxides. Selenium and its oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Skin and eye contact

Acute toxicity : Not classified

04/30/2015 EN (English US) 4/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Selenium (7782-49-2)	
LD50 oral rat	6700 mg/kg
ATE US (oral)	100.000 mg/kg body weight
ATE US (gases)	700.000 ppmV/4h
ATE US (vapors)	3.000 mg/l/4h
ATE US (dust, mist)	0.500 mg/l/4h

Water (7732-18-5)	
LD50 oral rat	≥ 90000 mg/kg
ATE US (oral)	90000.000 mg/kg body weight

Skin corrosion/irritation : Causes severe skin burns and eye damage. Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

Selenium (7782-49-2)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation : Irritation of the respiratory tract.

Symptoms/injuries after skin contact Burns. Yellow skin.

Symptoms/injuries after eye contact Causes serious eye damage.

Symptoms/injuries after ingestion : Burns. Central nervous system depression.

Central nervous system depression. Affection/discolouration of the teeth. Enlargement/affection Chronic symptoms

of the liver. Emotional instability.

SECTION 12: Ecological information

12.1. **Toxicity**

Selenium (7782-49-2)		
LC50 fish 1	<	
EC50 Daphnia 1	0.43 mg/l 48 h	
EC50 other aquatic organisms 1	99 mg/l 72 h	
LOEC (acute)	7.8 mg/l 96 h	
NOEC (acute)	2 mg/l 96 h	
Nitric Acid, 70% w/w (7697-37-2)		
LC50 fish 1	25 - 36 mg/l (96 h; Lepomis macrochirus; Pure substance)	
EC50 Daphnia 1	180 mg/l (48 h; Daphnia magna; Pure substance)	
LC50 fish 2	72 ppm (Gambusia affinis: Pure substance)	

Nitric Acid, 70% w/w (7697-37-2)	
LC50 fish 1	25 - 36 mg/l (96 h; Lepomis macrochirus; Pure substance)
EC50 Daphnia 1	180 mg/l (48 h; Daphnia magna; Pure substance)
LC50 fish 2	72 ppm (Gambusia affinis; Pure substance)
Threshold limit algae 1	> 19 mg/l (Algae; Pure substance)

Persistence and degradability 12.2.

Selenium AA Standard, 1000 ppm (1mL = 1mg Se)		
Persistence and degradability	Not readily biodegradable in water.	
Nitric Acid, 70% w/w (7697-37-2)		
Persistence and degradability	Biodegradability: not applicable. No test data on mobility of the components available.	
Biochemical oxygen demand (BOD)	Not applicable	
Chemical oxygen demand (COD)	Not applicable	

04/30/2015 EN (English US) 5/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Nitric Acid, 70% w/w (7697-37-2)	
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
Water (7732-18-5)	
Persistence and degradability Not established.	

12.3. Bioaccumulative potential

Selenium AA Standard, 1000 ppm (1mL = 1mg Se)			
Bioaccumulative potential	Potential for bioaccumulation (500 ≤ BCF ≤ 5000).		
Selenium (7782-49-2)	Selenium (7782-49-2)		
BCF fish 1	0.64 mg/l 60 d		
Bioconcentration factor (BCF REACH)	7.7		
Log Pow	5		
Nitric Acid, 70% w/w (7697-37-2)			
BCF fish 1	<= 1 (Pisces)		
Log Pow	-2.3 (OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method)		
Bioaccumulative potential	Bioaccumulation: not applicable.		
Water (7732-18-5)			
Bioaccumulative potential	Not established.		

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to comply with local, state and federal regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3264 Corrosive liquid, acidic, inorganic, n.o.s. (Nitric acid), 8, II

UN-No.(DOT) : UN3264

Proper Shipping Name (DOT) : Corrosive liquid, acidic, inorganic, n.o.s.

Transport hazard class(es) (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Hazard labels (DOT) : 8 - Corrosive

Packing group (DOT) : II - Medium Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Symbols : G - Identifies PSN requiring a technical name

04/30/2015 EN (English US) 6/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)

: B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T11 - 6 178.274(d)(2) Normal..... 178.275(d)(3)

TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: (image) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and a is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: (image) Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP27 - A portable tank having a minimum test pressure of 4 bar (400 kPa) may be used provided the calculated test pressure is 4 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

: 154

DOT Packaging Exceptions (49 CFR 173.xxx) DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

Colonium

No additional information available

SECTION 15: Regulatory information

SARA Section 311/312 Hazard Classes

15.1. US Federal regulations

Selenium AA Standard, 1000 ppm (1mL = 1mg Se)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Delayed (chronic) health hazard

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Seienium	CAS NO 7782-49-2	0.1		
Nitric Acid, 70% w/w	CAS No 7697-37-2	4		
Selenium (7782-49-2)				
Listed on United States SARA Section 313				
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb			

Immediate (acute) health hazard Delayed (chronic) health hazard

CAC No 7700 40 0

04/30/2015 EN (English US) 7/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Nitric Acid, 70% w/w (7697-37-2)	
Listed on United States SARA Section 313	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

15.2. International regulations

CANADA

Selenium (7782-49-2)		
Listed on the Canadian DSL (Domestic Substances List)		
Nitric Acid, 70% w/w (7697-37-2)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Class E - Corrosive Material Class C - Oxidizing Material	
Water (7732-18-5)		
Listed on the Canadian DSL (Domestic Substances List)		
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria	

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

National regulations

Nitric Acid, 70% w/w (7697-37-2)	
Listed on the Canadian IDL (Ingredient Disclosure List)	
Water (7732-18-5)	
Not listed on the Canadian IDL (Ingredient Disclosure List)	

15.3. US State regulations

California Proposition 65- This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

SECTION 16: Other information

Other information : None.

04/30/2015 EN (English US) 8/9

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases: see section 16:

Acute Tox. 3 (Inhalation)	Acute toxicity (inhalation) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Aquatic Chronic 4	Hazardous to the aquatic environment - Chronic Hazard Category 4
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Met. Corr. 1	Corrosive to metals Category 1
Ox. Liq. 3	Oxidizing liquids Category 3
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Corr. 1B	Skin corrosion/irritation Category 1B
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
H272	May intensify fire; oxidizer
H290	May be corrosive to metals
H301	Toxic if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H331	Toxic if inhaled
H373	May cause damage to organs through prolonged or repeated
	exposure
H413	May cause long lasting harmful effects to aquatic life
H272 H290 H301 H314 H318 H331	May intensify fire; oxidizer May be corrosive to metals Toxic if swallowed Causes severe skin burns and eye damage Causes serious eye damage Toxic if inhaled May cause damage to organs through prolonged or repeated exposure

NFPA health hazard : 3 - Short exposure could cause serious temporary or


residual injury even though prompt medical attention was

ven.

NFPA fire hazard : 0 - Materials that will not burn.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

* - Chronic (long-term) health effects may result from repeated overexposure

Flammability : 0 Minimal Hazard - Materials that will not burn

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT

react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal Protection : [

D - Face shield and eye protection, Gloves, Synthetic apron

SDS US (GHS HazCom 2012)

Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and LabChem Inc assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.

04/30/2015 EN (English US) 9/9