

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name. : Sulfuric Acid, 16.7% v/v

Product code : LC25605

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : For laboratory and manufacturing use only.

1.3. Details of the supplier of the safety data sheet

LabChem Inc

Jackson's Pointe Commerce Park Building 1000, 1010 Jackson's Pointe Court

Zelienople, PA 16063 - USA T 412-826-5230 - F 724-473-0647 info@labchem.com - www.labchem.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 or 011-703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin Corr. 1A H314 Eye Dam. 1 H318 Aquatic Acute 3 H402

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)



GHS05

Signal word (GHS-US) : Dange

Hazard statements (GHS-US) : H314 - Causes severe skin burns and eye damage

H402 - Harmful to aquatic life

Precautionary statements (GHS-US) : P260 - Do not breathe mist, vapours, spray

P264 - Wash exposed skin thoroughly after handling

P273 - Avoid release to the environment

P280 - Wear protective gloves, protective clothing, eye protection, face protection P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated

clothing. Rinse skin with water/shower

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing P310 - Immediately call a POISON CENTER/doctor/... P363 - Wash contaminated clothing before reuse

P405 - Store locked up

P501 - Dispose of contents/container to comply with local, state and federal regulations

2.3. Other hazards

Other hazards not contributing to the

classification

: None

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

10/08/2013 EN (English) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
Water	(CAS No) 7732-18-5	74.98	Not classified
Sulfuric Acid, 96% w/w	(CAS No) 7664-93-9	25.02	Skin Corr. 1A, H314 Eye Dam. 1, H318

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice

(show the label where possible).

First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. Immediately call a

POISON CENTER or doctor/physician.

First-aid measures after skin contact : Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

Immediately call a POISON CENTER or doctor/physician.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or

doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes severe skin burns and eye damage.

Symptoms/injuries after eye contact : Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Reactivity : Thermal decomposition generates : Corrosive vapours.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Avoid (reject) fire-fighting water to enter environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Safety glasses. Gloves. Protective clothing. Head/neck protection.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of

vapour. Do not breathe mist, vapours, spray. Avoid contact during pregnancy/while nursing.

Hygiene measures : Wash exposed skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.

10/08/2013 EN (English) 2/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : incompatible

materials. Keep container closed when not in use.

Incompatible products : metals. cyanides. Strong bases.

Incompatible materials : Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Sulfuric Acid, 96% w/w (7664	1-93-9)	
USA ACGIH	ACGIH TWA (mg/m³)	0.2 mg/m³
USA OSHA	OSHA PEL (TWA) (mg/m³)	1 mg/m³

8.2. Exposure controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity

of any potential exposure. Provide adequate general and local exhaust ventilation.

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection : Wear protective gloves.

Eye protection : Chemical goggles or face shield.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Wear appropriate mask.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear, colorless liquid.

Colour : Colourless.
Odour : None.

No data available Odour threshold рΗ No data available Relative evaporation rate (butylacetate=1) : No data available Melting point : No data available No data available Freezing point **Boiling point** No data available Flash point : No data available Self ignition temperature : No data available : No data available Decomposition temperature Flammability (solid, gas) : No data available Vapour pressure : No data available Relative vapour density at 20 °C : No data available Relative density No data available Density 1.18 a/ml

Density : 1.18 g/ml
Solubility : Soluble in water.
Log Pow : No data available
Log Kow : No data available

Viscosity, kinematic : 1.48 cSt

Viscosity, dynamic : No data available Explosive properties : Not applicable.

Oxidising properties : None.

Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Thermal decomposition generates: Corrosive vapours.

10/08/2013 EN (English) 3/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reacts violently with (some) bases: release of heat.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

metals. cyanides. Strong bases.

10.6. Hazardous decomposition products

Sulfur compounds. Thermal decomposition generates: Corrosive vapours.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Sulfuric Acid, 96% w/w (7664-93-9)	
LD50 oral rat	2140 mg/kg bodyweight (Rat; Experimental value,Rat; Experimental value)
Water (7732-18-5)	

Water (1132-10-3)	
LD50 oral rat	≥ 90000 mg/kg
Skin corrosion/irritation	Causes severe skin burns and eye damage.
Serious eve damage/irritation	Causes serious eve damage.

Respiratory or skin sensitisation : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

Sulfuric Acid, 96% w/w (7664-93-9)	
IARC group	1
Reproductive toxicity	: Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated : Not classified

exposure)

Aspiration hazard : Not classified

Potential Adverse human health effects and : Based on av

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/injuries after eye contact : Causes serious eye damage.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Harmful to aquatic life.

Sulfuric Acid, 96% w/w (7664-93-9)	
LC50 fishes 1	42 mg/l (96 h; Gambusia affinis)
EC50 Daphnia 1	29 mg/l (24 h; Daphnia magna)
LC50 fish 2	49 mg/l (48 h; Lepomis macrochirus)
TLM fish 1	42 mg/l (96 h; Gambusia affinis)
Threshold limit other aquatic organisms 1	6900 mg/l (24 h; Pseudomonas fluorescens)

12.2. Persistence and degradability

Sulfuric Acid, 16.7% v/v	
Persistence and degradability	Not established.
Sulfuric Acid, 96% w/w (7664-93-9)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

10/08/2013 EN (English) 4/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential	
Sulfuric Acid, 16.7% v/v	
Bioaccumulative potential	Not established.
Sulfuric Acid, 96% w/w (7664-93-9)	
Log Pow	-2.20 (Estimated value)
Bioaccumulative potential	Bioaccumulation: not applicable.

Mobility in soil

No additional information available

Other adverse effects 12.5.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

Waste treatment methods

: Dispose in a safe manner in accordance with local/national regulations. Dispose of Waste disposal recommendations

contents/container to comply with local, state and federal regulations.

: Avoid release to the environment. Ecology - waste materials

SECTION 14: Transport information

In accordance with DOT

14.1. **UN** number

UN-No.(DOT) 2796 DOT NA no. UN2796

UN proper shipping name

DOT Proper Shipping Name : Sulfuric acid

with not more than 51% acid

Department of Transportation (DOT) Hazard

Classes

: 8 - Class 8 - Corrosive material 49 CFR 173.136

Hazard labels (DOT) : 8 - Corrosive substances



Packing group (DOT)

DOT Special Provisions (49 CFR 172.102)

: II - Medium Danger

A3 - For combination packagings, if glass inner packagings (including ampoules) are used, they must be packed with absorbent material in tightly closed metal receptacles before packing in outer packagings.

A7 - Steel packagings must be corrosion-resistant or have protection against corrosion.

B2 - MC 300, MC 301, MC 302, MC 303, MC 305, and MC 306 and DOT 406 cargo tanks are not authorized

B15 - Packagings must be protected with non-metallic linings impervious to the lading or have a suitable corrosion allowance.

IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

N6 - Battery fluid packaged with electric storage batteries, wet or dry, must conform to the packaging provisions of 173.159 (g) or (h) of this subchapter.

N34 - Aluminum construction materials are not authorized for any part of a packaging which is normally in contact with the hazardous material.

T8 - 4 178.274(d)(2) Normal......Prohibited TP2 - a. The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 95 / (1 + a (tr - tf)) Where: tr is the maximum mean bulk temperature during transport, tf is the temperature in degrees celsius of the liquid during filling, and is the mean coefficient of cubical expansion of the liquid between the mean temperature of the liquid during filling (tf) and the maximum mean bulk temperature during transportation (tr) both in degrees celsius. b. For liquids transported under ambient conditions may be calculated using the formula: a = (d15 - d50) / 35*d50 Where: d15 and d50 are the densities (in units of mass per unit volume) of the liquid at 15 C (59 F) and 50 C (122 F), respectively.

TP12 - This material is considered highly corrosive to steel.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154 DOT Packaging Non Bulk (49 CFR 173.xxx) : 202 DOT Packaging Bulk (49 CFR 173.xxx) : 242

10/08/2013 EN (English) 5/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.3. Additional information

Other information : No supplementary information available.

Overland transport

No additional information available

Transport by sea

DOT Vessel Stowage Location

: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 1 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

Sulfuric Acid, 16.7% v/v	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

Sulfuric Acid, 96% w/w (7664-93-9)	
Listed on the United States TSCA (Toxic Substan	nces Control Act) inventory
RQ (Reportable quantity, section 304 of EPA's List of Lists) :	1000 lb
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

15.2. International regulations

CANADA

Sulfuric Acid, 16.7% v/v	
WHMIS Classification	Class E - Corrosive Material

Sulfuric Acid, 96% w/w (7664-93-9)

Listed on the Canadian DSL (Domestic Sustances List) invento
--

WHMIS Classification Class E - Corrosive Material

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

15.2.2. National regulations

Sulfuric Acid, 96% w/w (7664-93-9)

Listed on the Canadian Ingredient Disclosure List

15.3. US State regulations

Sulfuric Acid, 96% w/w (7664-93-9)

SECTION 16: Other information

Other information : None.

10/08/2013 EN (English) 6/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases: see section 16:

Aquatic Acute 3	Hazardous to the aquatic environment — AcuteHazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H402	Harmful to aquatic life

NFPA health hazard : 3 - Short exposure could cause serious temporary or


residual injury even though prompt medical attention was

given.

NFPA fire hazard : 0 - Materials that will not burn.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions,

and are not reactive with water.



HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 0 Minimal Hazard Physical : 0 Minimal Hazard

Personal Protection : H

SDS US (GHS HazCom 2012)

Information in this SDS is from available published sources and is believed to be accurate. No warranty, express or implied, is made and LabChem Inc assumes no liability resulting from the use of this SDS. The user must determine suitability of this information for his application.

10/08/2013 EN (English) 7/7