

Product Specification

Bromide Standard, 1000 ppm Br

Manufacture Date: N/A

Lot Number: SAMPLE

Product Number: 1180

Expiration Date: N/A

The certified value reported is the prepared value based upon the method of preparation of the material. The uncertainty in the prepared value is based upon the volumetric method of preparation.

| Name | CAS# | Grade |
|----------------|-----------|-----------------|
| Water | 7732-18-5 | ACS/ASTM/USP/EP |
| Sodium Bromide | 7647-15-6 | High Purity |
| | | |

| Test | Specification | Result |
|--------------|------------------|--------|
| Appearance | Colorless liquid | N/A |
| Bromide (Br) | 995-1005 ppm | N/A |

| Specification | Reference |
|------------------------------------------------|---------------------|
| Bromide Solution, Standard (1 mL = 1 mg Br-) | ASTM (D 3869 D) |
| Standard Bromide Solution, 1000 mg/L | APHA (4110 B) |
| Bromide Stock Solution (1.00 mL = 1.00 mg Br-) | EPA (SW-846) (9056) |
| Sodium Bromide Standard Solution, 1000 mg/L | ASTM (D 1246) |
| Bromide Stock Solution (1.00 mL = 1.00 mg Br?) | ASTM (D 4327) |

Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with ε thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

| Part Number | Size / Package Type | Shelf Life (Unopened Container) |
|-------------|---------------------|---------------------------------|
| 1180-4 | 120 mL natural poly | 18 months |
| 1180-8 | 250 mL natural poly | 18 months |
| 1180-16 | 500 mL natural poly | 18 months |
| | | |

Recommended Storage: 15°C - 30°C (59°F - 86°F)

KatietSchnun

Katie Schnur Quality Control Manager

This Certificate of Analysis is designed to comply with ISO Guide 31 "Reference Materials -- Contents of Certificates and Labels."