

Arlington, TX 76012
Pocomoke City, MD 21851
Batesville, IN 47006
http://www.riccachemical.com
1-888-GO-RICCA
customerservice@riccachemical.com

Product Specification

Silver Nitrate, 0.0192 Normal (0.0192 Molar), 1 mL = 1 mg CN

Lot Number: SAMPLE Product Number: 6910

Manufacture Date: N/A

Expiration Date: N/A

| Name | CAS# | Grade |
|----------------|-----------|-----------------|
| Water | 7732-18-5 | ACS/ASTM/USP/EP |
| Silver Nitrate | 7761-88-8 | ACS |

| Test | Specification | Result | NIST SRM# |
|--|---------------------------|--------|-----------|
| Appearance | Colorless liquid | N/A | |
| Assay (vs. Potassium Chloride/Potassium Chromate) | 0.01919-0.01921 N at 20°C | N/A | 999 |

| Specification | Reference |
|--|------------------------|
| Standard Silver Nitrate Titrant, 1.00 mL = 1.00 mg CN- | APHA (4500-CN- D) |
| Standard Silver Nitrate Solution (0.0192 N) | EPA (SW-846) (9014) |
| Silver Nitrate Solution (0.0192 N) | EPA (SW-846) (7.3.3.2) |
| Standard Silver Nitrate Solution, 0.0192 N | EPA (335.2) |
| Silver Nitrate Solution, Standard (1 mL = 1 mg CN-) | ASTM (D 4282) |
| Silver Nitrate Solution 0.0192 N Standard | ASTM (D 4374) |

Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with \$\epsilon\$ thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

| Part Number | Size / Package Type | Shelf Life (Unopened Container) |
|-------------|---------------------|---------------------------------|
| 6910-32 | 1 L amber poly | 24 months |
| 6910-1 | 4 L black poly | 24 months |
| 6910-16 | 500 mL amber poly | 24 months |

Recommended Storage: 15°C - 30°C (59°F - 86°F)

KatietSchnun

Katie Schnur

Quality Control Manager

This Certificate of Analysis is designed to comply with ISO Guide 31 "Reference Materials -- Contents of Certificates and Labels."

Version: 1.3 Lot Number: SAMPLE Product Number: 6910 Page 1 of 1