# SIGMA-ALDRICH

sigma-aldrich.com

# SAFETY DATA SHEET

Version 5.13 Revision Date 10/12/2015 Print Date 11/11/2015

# **1. PRODUCT AND COMPANY IDENTIFICATION**

1.1	Product identifiers Product name	:	Petroleum ether
	Product Number Brand	:	77399 Sigma-Aldrich
	CAS-No.	:	101316-46-5
12	Relevant identified use	s of th	e substance or mixture and uses

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	: Laboratory chemicals, Synthesis of substances
-----------------	---

#### 1.3 Details of the supplier of the safety data sheet

Company	:	Sigma-Aldrich 3050 Spruce Street SAINT LOUIS MO 63103 USA
Telephone	:	+1 800-325-5832
Fax	:	+1 800-325-5052
Emergency telephone n	ımbe	er

# 1.4 Emergency telephone number

	Emergency Phone #	: (314) 776-6555
--	-------------------	------------------

# 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

#### GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 1), H224 Skin irritation (Category 2), H315 Reproductive toxicity (Category 2), H361 Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336 Specific target organ toxicity - repeated exposure, Inhalation (Category 2), H373 Aspiration hazard (Category 1), H304 Acute aquatic toxicity (Category 2), H401 Chronic aquatic toxicity (Category 2), H411

For the full text of the H-Statements mentioned in this Section, see Section 16.

Danger

# 2.2 GHS Label elements, including precautionary statements

Pictogram

Signal word



0	5
Hazard statement(s)	
H224	Extremely flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure if
	inhaled.

H411	Toxic to aquatic life with long lasting effects.
Precautionary statement(s)	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and
	understood.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P260	Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/ protective clothing/ eye protection/ face
	protection.
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/
	physician.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing.
	Rinse skin with water/shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for
	breathing. Call a POISON CENTER or doctor/ physician if you feel
	unwell.
P308 + P313	IF exposed or concerned: Get medical advice/ attention.
P331	Do NOT induce vomiting.
P332 + P313	If skin irritation occurs: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to
	extinguish.
P391	Collect spillage.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

# **2.3 Hazards not otherwise classified (HNOC) or not covered by GHS** Repeated exposure may cause skin dryness or cracking.

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

### 3.1 Substances

Synonyms	: Petroleum be	nzin
CAS-No. EC-No.	: 101316-46-5 : 309-852-0	

# Hazardous components

Component	Classification	Concentration
Petroleum ether, Bp 30 - 60°C		
	Flam. Liq. 1; Skin Irrit. 2; Repr. 2; STOT SE 3; STOT RE 2; Asp. Tox. 1; Aquatic Acute 2; Aquatic Chronic 2; H224, H304, H315, H336, H361, H373, H411	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

# 4. FIRST AID MEASURES

#### 4.1 Description of first aid measures

#### **General advice**

Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.

#### If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

#### In case of skin contact

Wash off with soap and plenty of water. Consult a physician.

#### In case of eye contact

Flush eyes with water as a precaution.

#### If swallowed

Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

#### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

#### **4.3 Indication of any immediate medical attention and special treatment needed** No data available

## **5. FIREFIGHTING MEASURES**

#### 5.1 Extinguishing media

# Suitable extinguishing media

Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

5.2 Special hazards arising from the substance or mixture Nature of decomposition products not known.

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### 5.4 Further information

Use water spray to cool unopened containers.

# 6. ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

#### 6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

#### 6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

#### 6.4 Reference to other sections

For disposal see section 13.

# 7. HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Avoid contact with skin and eyes. Avoid inhalation of vapour or mist.

Use explosion-proof equipment.Keep away from sources of ignition - No smoking.Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

# 7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Storage class (TRGS 510): Flammable liquids

#### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

# **Components with workplace control parameters** Contains no substances with occupational exposure limit values.

# 8.2 Exposure controls

#### Appropriate engineering controls

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

#### Personal protective equipment

#### **Eye/face protection**

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

#### Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 480 min Material tested:Camatril® (KCL 730 / Aldrich Z677442, Size M)

Splash contact Material: Nitrile rubber Minimum layer thickness: 0.2 mm Break through time: 52 min Material tested:Dermatril® P (KCL 743 / Aldrich Z677388, Size M)

data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374

If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

#### **Body Protection**

Complete suit protecting against chemicals, Flame retardant antistatic protective clothing., The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

#### **Respiratory protection**

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multipurpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

#### Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

		···· ··· · ··· · · · · · · · · · · · ·
a)	Appearance	Form: liquid Colour: colourless
b)	Odour	phenol-like
c)	Odour Threshold	No data available
d)	рН	No data available
e)	Melting point/freezing point	< -29.99 °C (< -21.98 °F)
f)	Initial boiling point and boiling range	30 °C (86 °F)
g)	Flash point	-48.99 °C (-56.18 °F) - closed cup
h)	Evaporation rate	No data available
i)	Flammability (solid, gas)	No data available
j)	Upper/lower flammability or explosive limits	Upper explosion limit: 7.5 %(V) Lower explosion limit: 1.2 %(V)
k)	Vapour pressure	500 hPa (375 mmHg)
I)	Vapour density	No data available
m)	Relative density	0.63 g/mL at 20 °C (68 °F)
n)	Water solubility	insoluble
o)	Partition coefficient: n- octanol/water	log Pow: 4.0
p)	Auto-ignition temperature	No data available
q)	Decomposition temperature	No data available
r)	Viscosity	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	No data available
Other safety information No data available		

# **10. STABILITY AND REACTIVITY**

10.1	Reactivity
	No data available

9.2

- **10.2 Chemical stability** Stable under recommended storage conditions.
- **10.3 Possibility of hazardous reactions** Vapours may form explosive mixture with air.
- **10.4 Conditions to avoid** Heat, flames and sparks.
- **10.5** Incompatible materials Oxidizing agents
- **10.6 Hazardous decomposition products** Other decomposition products - No data available

# **11. TOXICOLOGICAL INFORMATION**

#### 11.1 Information on toxicological effects

#### Acute toxicity

No data available

Inhalation: No data available

Dermal: No data available

No data available

# Skin corrosion/irritation

Skin - Rabbit Result: Skin irritation

#### Serious eye damage/eye irritation No data available

**Respiratory or skin sensitisation** No data available

#### Germ cell mutagenicity No data available

# Carcinogenicity

- IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
- NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

#### **Reproductive toxicity**

Suspected human reproductive toxicant

No data available

## Specific target organ toxicity - single exposure

Skin contact - May cause drowsiness or dizziness.

# Specific target organ toxicity - repeated exposure

Inhalation - May cause damage to organs through prolonged or repeated exposure.

#### Aspiration hazard

May be fatal if swallowed and enters airways.

# **Additional Information**

RTECS: Not available

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

# **12. ECOLOGICAL INFORMATION**

# 12.1 Toxicity

- 12.2 Persistence and degradability No data available
- **12.3 Bioaccumulative potential** No data available

#### 12.4 Mobility in soil

No data available

#### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

#### 12.6 Other adverse effects

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

# **13. DISPOSAL CONSIDERATIONS**

#### 13.1 Waste treatment methods

#### Product

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

#### Contaminated packaging

Dispose of as unused product.

# 14. TRANSPORT INFORMATION

#### DOT (US)

UN number: 1268 Class: 3 Packing group: I Proper shipping name: Petroleum distillates, n.o.s. Reportable Quantity (RQ):

Poison Inhalation Hazard: No

#### IMDG

UN number: 1268 Class: 3 Packing group: I EMS-No: F-E, S-E Proper shipping name: PETROLEUM DISTILLATES, N.O.S. (Hydrocarbon mixture C5-C8 Aliphates) Marine pollutant: yes IATA UN number: 1268 Class: 3 Packing group: I Proper shipping name: Petroleum distillates, n.o.s.

# **15. REGULATORY INFORMATION**

#### SARA 302 Components

No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

#### SARA 313 Components

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

#### Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

#### Pennsylvania Right To Know Components

Petroleum ether, Bp 30 - 60°C	CAS-No. 101316-46-5	Revision Date
New Jersey Right To Know Components		
Petroleum ether, Bp 30 - 60°C	CAS-No. 101316-46-5	Revision Date

#### California Prop. 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

# **16. OTHER INFORMATION**

#### Full text of H-Statements referred to under sections 2 and 3.

Aquatic Acute Aquatic Chronic	Acute aquatic toxicity Chronic aquatic toxicity
Asp. Tox.	Aspiration hazard
Flam. Liq.	Flammable liquids
H224	Extremely flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
Repr.	Reproductive toxicity

#### **HMIS Rating**

Health hazard: Chronic Health Hazard:	2 *
Flammability:	4
Physical Hazard	0
NFPA Rating	
NFPA Rating Health hazard:	2
•	2 4

#### **Further information**

Copyright 2015 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only. The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.sigma-aldrich.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

#### **Preparation Information**

Sigma-Aldrich Corporation Product Safety – Americas Region 1-800-521-8956

Version: 5.13

Revision Date: 10/12/2015

Print Date: 11/11/2015